









Plastic distribution box ESP4 series (M12 socket, with pre-wired cable)

Description:				
Plastic housing, 4-way, pre-wired cable, single/double signal.				
Features:				
<ul style="list-style-type: none"> Optional output (PNP/NPN) LED indicator and high protection class IP67 Standard 3m PUR cable, optional cable length 				
				
Type List	ESP4-12-2P-3/P	ESP4-12-2N-3/P	ESP4-12-3P-3/P	ESP4-12-3N-3/P
Technical Data				
Output Function	1 signal		2 signals	
Output Type	PNP	NPN	PNP	NPN
Connection for Sensors/Actuators	4-pin M12 female		5-pin M12 female	
Locking Sockets	Threaded M12x1			
Dimensions	Fig.1			
Pin Assignment	Fig.2		Fig.3	
Wiring Diagram	Fig.4	Fig.5	Fig.6	Fig.7
Supply Voltage	10...30VDC (24VDC)			
Supply Voltage Indicator	LED green			
I/O Channels	4			
Signals per Port	1		2	
Status Indicators	LED yellow			
Operating Current	Max. 2A			
Current Parameter	Max. 8A			
	Please do not operate cables above max. load capacity.			
Housing Material	Plastic			
	PC + ABS			
Protection Class	IP67			
Temperature Range	-40...+80°C			
Resistance	Good resistance against chemicals and oils. The resistance to aggressive media should be individually verified for your application.			
Cable Material	Standard PUR / PP Bending≥5 million			
Length	3m			
Dimensions				
Fig. 1				

Pin Assignment	
Fig. 2	Fig. 3
<p>4-pin</p> 	<p>5-pin</p> 
Wiring Diagram	
Fig. 4 Cable	 <p>LED indicator PNP</p>
Fig. 5 Cable	 <p>LED indicator NPN</p>
Fig. 6 Cable	 <p>LED indicator PNP</p>
Fig. 7 Cable	 <p>LED indicator NPN</p>