

Field-attachable I/O Connector-M8 (Angled-female)

Description:

Used for sensors and I/O connecting. Standard threaded connection. Designed with the female port. 3,4-core are available. Degree of protection IP67.

Features:

- Flexible welding joints and pin contact.



Type Code

Cable jacket	Description	Type	Pin	Rated current/voltage	Cable φ
PA	Female 3-core	LSBO8.3-0/C	3	4A/60V	3.5-5mm
	Female 4-core	LSBO8.4-0/C	4	4A/30V	3.5-5mm

Selection Instructions

LSBO8.3 - 0/C

Attn: Standard

Additional Information

- Cross section of core for welded connection , max.0.25mm²
- To connected into distribution box or IP 67 modular, match the internal mistake-proofing slot.
- "A6" connector : length of peeled jacket 12mm, length of peeled wire 3mm.

Field-attachable I/O Connector-M8 (Angled-male)

Description:

Used for sensors and I/O connecting. Standard threaded connection. Designed with the male port. 3,4-core are available. Degree of protection IP67.

Features:

- Flexible welding joints and pin contact.



Type Code

Cable jacket	Description	Type	Pin	Rated current/voltage	Cable φ
PA	Male 3-core	LSB8.3-0/C	3	4A/60V	3.5-5mm
	Male 4-core	LSB8.4-0/C	4	4A/30V	3.5-5mm

Selection Instructions

LSB8.3 - 0/C

Attn: Standard

Additional Information

- Cross section of core for welded connection , max.0.25mm²
- To connected into distribution box or IP 67 modular, match the internal mistake-proofing slot.
- "A6" connector : length of peeled jacket 12mm, length of peeled wire 3mm.