

Plastic distribution box ESP6 series (M8 socket, with M12 plug connector)

Description:		
Plastic housing, distributed design, 6-way, single signal.		
Features:		
<ul style="list-style-type: none"> Optional output (PNP/NPN) LED indicator and high protection class IP67 Compact size - 110mm, especially suitable for small space installation Standard 3m PUR cable for M12 connector, optional cable material and length 		
Type List		
Type List	ESP6-8-2P-Q12	ESP6-8-2N-Q12
Technical Data		
Output Function	1 signal	
Output Type	PNP	NPN
Connection for Sensors/Actuators	3-pin M8 female	
Locking Sockets	Threaded M8x1	
Dimensions	Fig. 1	
Pin Assignment	Fig. 2	
Wiring Diagram	Fig. 6	Fig. 7
Supply Voltage	10...30VDC (24VDC)	
Supply Voltage Indicator	LED green	
I/O Channels	6	
Signals per Port	1	
Status Indicators	LED yellow	
Operating Current	Max. 1.5A	
Current Parameter	Max. 1.5A	
	Please do not operate cables above max. load capacity.	
Housing Material	Plastic	
	PC + ABS	
Protection Class	IP67	
Temperature Range	-40...+80°C	
Resistance	Good resistance against chemicals and oils. The resistance to aggressive media should be individually verified for your application.	
Connector	M12(12pins)	
Dimensions		Pin Assignment
Fig. 1		Fig. 2



Accessories of Distribution Box -Connector																												
Type List																												
Type	CO12.12-3 / P	CBO12.12-3 / P																										
Description	Straight pre-wired connector	Angled pre-wired connector																										
Cable Material	Standard PUR / PP Bending≥5 million																											
Cable Length	3m																											
Dimensions	Fig. 3	Fig. 4																										
Pin Assignment	Fig. 5																											
Dimensions																												
	Fig. 3 	Fig. 4 																										
Pin Assignment																												
	Fig. 5 	<table border="1"> <thead> <tr> <th>12-pin M12 Male</th> <th>Suggested Cable Color</th> </tr> </thead> <tbody> <tr><td>1</td><td>BN</td></tr> <tr><td>2</td><td>BU</td></tr> <tr><td>3</td><td>WH</td></tr> <tr><td>4</td><td>GN</td></tr> <tr><td>5</td><td>PK</td></tr> <tr><td>6</td><td>YE</td></tr> <tr><td>7</td><td>BK</td></tr> <tr><td>8</td><td>GY</td></tr> <tr><td>9</td><td>RD</td></tr> <tr><td>10</td><td>VT</td></tr> <tr><td>11</td><td>GY/PK</td></tr> <tr><td>12</td><td>RD/BU</td></tr> </tbody> </table>	12-pin M12 Male	Suggested Cable Color	1	BN	2	BU	3	WH	4	GN	5	PK	6	YE	7	BK	8	GY	9	RD	10	VT	11	GY/PK	12	RD/BU
12-pin M12 Male	Suggested Cable Color																											
1	BN																											
2	BU																											
3	WH																											
4	GN																											
5	PK																											
6	YE																											
7	BK																											
8	GY																											
9	RD																											
10	VT																											
11	GY/PK																											
12	RD/BU																											
Wiring Diagram																												
Fig. 6 Connector																												
	LED indicator PNP																											
Fig. 7 Connector																												
	LED indicator NPN																											